

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 March 2001 (08.03.2001)

PCT

(10) International Publication Number  
**WO 01/16623 A1**

(51) International Patent Classification<sup>7</sup>: G01V 1/38, B63B 21/66

(21) International Application Number: PCT/NO00/00244

(22) International Filing Date: 20 July 2000 (20.07.2000)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:  
19993971 17 August 1999 (17.08.1999) NO

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): PETROLEUM GEO-SERVICES AS [NO/NO]; Strandveien 4, N-1324 Lysaker (NO).


Published:  
— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and  
(75) Inventor/Applicant (*for US only*): SEMB, Ole, Fredrik [NO/NO]; Langgaten 27, N-3080 Holmestrand (NO).

(74) Agent: ABC-PATENT, SIVILING. ROLF CHR. B. LARSEN A.S.; Brynsveien 5, N-0667 Oslo (NO).

(54) Title: SYSTEM FOR CONTROLLING A MARINE SEISMIC ARRAY



(57) Abstract: System for controlling seismic arrays comprising at least one deflector coupled to one side of the towing vessel through at least one wire, lead-in or similar, the detector being positioned at a distance perpendicular to the vessel's direction of movement, the vessel being provided with a navigation system for measuring the position of the vessel. The vessel comprises calculation means for, on the basis of the vessel's position, calculating deviations in vessel's position from a predetermined path. The wire is coupled to the vessel through control organs, e.g. a winch, adapted to vary the wire length from the vessel to the deflector. The control organs are coupled to the calculation means for adjusting the wire length based on the deviations in the position of the towing vessel, thus to avoid corresponding deviations in the movements of the deflector.

WO 01/16623 A1